

# Reliability evaluation of non-isolated high gain interleaved DC-DC converter

Subbulakshmy Ramamurthi, Palanisamy Ramasamy

Department of Electrical and Electronics Engineering, SRM Institute of Science and Technology, Kattankulathur, Chennai, India

## Article Info

### Article history:

Received Apr 26, 2023

Revised Sep 21, 2023

Accepted Oct 6, 2023

### Keywords:

DC-DC converter

High gain

Interleaved and non-isolated

Mean time between failures

Reliability

## ABSTRACT

A high gain DC-DC converter is the crucial part in renewable energy systems (RES) and in electric vehicular systems. The reliability of those high-gain converters needs to be assessed for the long-term operation of renewable energy systems. This article presents the reliability analysis of non-isolated high gain interleaved DC-DC converter. The analysis primarily relies on calculating the mean time between failures (MTBF). Based on military handbook (MIL-HDBK-217) criteria, the reliability calculation is performed. Stress factors and predicted failure rate for each component of presented converter is evaluated and tabulated. Reliability evaluation is performed for 1.5 kW hardware prototype. Based on reliability evaluation results, a reliable converter with better operating life time has been introduced.

This is an open access article under the [CC BY-SA](https://creativecommons.org/licenses/by-sa/4.0/) license.



## Corresponding Author:

Palanisamy Ramasamy

Department of Electrical and Electronics Engineering, SRM Institute of Science and Technology

Kattankulathur, 603203, India

Email: krspalani@gmail.com

## NOMENCLATURE

$\lambda_{\text{Converter}}$ : failure rate of converter (FIT)

$\lambda_{\text{MOSFET}}$ : failure rate of MOSFET (FIT)

$\lambda_{\text{Diode}}$ : failure rate of diode (FIT)

$\lambda_{\text{Capacitor}}$ : failure rate of capacitor (FIT)

$\lambda_{\text{Inductor}}$ : failure rate of inductor (FIT)

$P_{\text{Switch Loss}}$ : switching loss of MOSFET (W)

$P_{\text{Diode}}$ : loss of diode (W)

$P_{\text{Capacitor Loss}}$ : loss of capacitor (W)

$P_{\text{CI}}$ : loss of coupled inductor (W)

$T_j$ : worst case junction temperature (°C)

$T_c$ : case temperature (°C)

$\theta_{jc}$ : junction to case thermal resistance (°C/W)

$P_d$ : power dissipation (W)

$\lambda$ : failure rate

$\lambda_b$ : base failure rate

$\pi_T$ : temperature factor

$\pi_A$ : application factor

$\pi_Q$ : quality factor

$\pi_E$ : environmental factor

$\pi_S$ : voltage stress factor

$\pi_C$ : construction factor

$\pi_{CV}$ : capacitance factor

$S$ : ratio of operating to rated voltage

$T_{HS}$ : hot spot temperature (°C)

$T_A$ : inductive device ambient operating temperature (°C)

$W_L$ : power loss of inductor (W)

$A$ : radiating surface area of case (in<sup>2</sup>)

$\Delta T$ : average temperature rise above ambient (°C)

## 1. INTRODUCTION

High gain DC-DC converters and inverters play a vital role in renewable energy systems (RES) and in electric vehicular systems [1]–[6]. Many types of converters were dealt in [7]–[9]. The employed DC-DC converters and inverters should be reliable to guarantee the sustainability of renewable energy systems and electric vehicular systems. The converters are built with semiconductor switches, inductors and capacitors in [10]–[13]. When DC-DC converters are put through any applications, there is a possibility that they will break down by many factors like switching losses of semiconductor switches, high reverse recovery problem of diodes, high capacitor stress, operative temperature of inductors and other external environmental conditions. Renewable energy applications rely on both converters and inverters. In particular, inverters play a crucial role in the overall process. Many types of inverter were proposed in [14]–[18]. Renewable energy-based converters must operate reliably for many years. Thus, it is imperative to evaluate the reliability of a DC-DC converter.

Efficiency, reliability, and price are the performance criteria for evaluating power converters which are presented in [19]–[24]. The probability of a system functions satisfactorily over time and under particular operational and environmental conditions is the standard way to assess dependability is given in [20]–[22]. The reliability study enables comparison of various design techniques, evaluation of the system design process, and definition of preventive maintenance plans. Reliability analysis is performed for conventional and interleaved DC-DC boost converters in [19]. The performance and reliability enhancement of modular DC converter were analysed in [20]. Many conventional dc converters are reconfigured and restructured their reliability performance are discussed in [21], [22]. The reliability assessment for multilevel DC converters are analyzed in [23]. Likewise, many articles in [19]–[23] have evaluated the reliability of DC converters. Life time extension of many converters can be made possible by using multistate markov analysis elucidated in [24].

This paper presents the reliability evaluation of high gain interleaved DC-DC converter. The operation, steady state analysis, power loss and efficiency of proposed converter were presented in [25]. The military manual MIL-HDBK-217F [26] is used to assess the reliability. This handbook is a basic supporting tool for the prediction of reliability of any electronic system. The stress factors and predicted failure rate of presented high gain interleaved DC-DC converter is calculated under normal operating conditions. Figure 1(a) shows the components of proposed converter included in reliability evaluation and Figure 1(b) shows the steps to be followed for the reliability evaluation. Typically, failure rates for each component are determined separately and then summed to determine the failure rate.




Figure 1. Reliability evaluation: (a) components included and (b) steps of reliability analysis

## 2. NOVEL NON-ISOLATED INTERLEAVED HIGH GAIN DC-DC CONVERTER

The operation, steady state analysis, power loss and efficiency calculations of proposed non-isolated interleaved high gain DC-DC converter is presented in [25]. The presented converter has interleaved structure, switched capacitor (SC) cell, passive clamp circuit and voltage multiplier unit (VMU). Through the use of the interleaving technique, the distribution of currents is optimized, and the occurrence of ripples is minimized. The SC cell improve the overall output voltage. Clamp circuits can reduce switching losses and voltage spikes caused by power switches being turned off. VMU further improves the overall voltage gain of the converter. It can able to obtain the output voltage of 515 V from 30 V input. The voltage gain of proposed converter is found to be 17.5 at a nominal duty ratio  $D = 0.6$ . The reliability evaluation is performed for the 1.5 kW hardware prototype. Figure 2 shows the circuit of non-isolated interleaved high gain DC-DC converter.




Figure 2. Circuit of non-isolated interleaved high gain DC-DC converter [25]

### 3. RELIABILITY EVALUATION

The reliability of the proposed converter is determined using the MIL-HDBK-217F military manual. The impact of power loss on the failure rates of converter components has been evaluated, and the failure rates of components are determined through practical calculations. In order to conduct a reliability analysis, it's important to know the component ratings of the converters. The components considered for reliability evaluation are illustrated in Figure 1(a), consisting of 2 coupled inductors, 2 MOSFETs, 7 diodes, and 6 capacitors. The reliability evaluation is conducted in accordance with the steps outlined in Figure 1(b). Reliability analysis of proposed converter is calculated under normal operating and environmental condition. Reliability of converter depends on manufacturing process and material used in devices and has an indirect impact by the working environment. The MTTF is estimated by (1) and (2):

$$\text{Mean Time of Failure} = \frac{1}{\lambda_{\text{Converter}}} \quad (1)$$

$$\lambda_{\text{Converter}} = \sum_{i=1}^2 \lambda_{\text{MOSFET}} + \sum_{j=1}^7 \lambda_{\text{Diode}} + \sum_{k=1}^6 \lambda_{\text{Capacitor}} + \sum_{l=1}^4 \lambda_{\text{Inductor}} \quad (2)$$

Failure rates and stress factors are dependent on environmental conditions. For the calculations of failure rate and stress factors, the power loss equations must be derived by using hardware parameters. The power loss values for switches ( $P_{\text{Switch Loss}}$ ), diodes ( $P_{\text{Diode Loss}}$ ), coupled inductor ( $P_{\text{CI Loss}}$ ) and capacitor ( $P_{\text{Capacitor Loss}}$ ) were calculated. Power loss equations and its values of proposed converter is shown in Table 1. For determining the MTTF of proposed converter, the failure rate of individual components like MOSFET's, diodes, capacitors and inductors of proposed is determined based on the equations tabulated in Table 2. Those equations are taken from MIL-HDBK-217 military handbook [26].

Table 1. Power loss equations and its values [25]

S. No	Equations	Loss values (W)
1.	$P_{\text{Switch Loss}} = I_D^2 \cdot R_{DS(ON)} + P_{\text{Switch (on)}} + P_{\text{Switch (off)}}$	17.95
2.	$P_{\text{Diode Loss}} = V_{\text{Diode (ON)}} \cdot I_{\text{Diode Avg}} + I_D^2 \cdot R_{\text{diode}}$	15.97
3.	$P_{\text{CI Loss}} = I_{LP}^2 \cdot R_{LP} + I_{LS}^2 \cdot R_{LS} + P_{\text{Core Loss}}$	9.11
4.	$P_{\text{Capacitor Loss}} = I_{C(RMS)}^2 \cdot ESR$	18.2
Total loss		61.23

The essential parameters and selected values of hardware components for failure rate for reliability assessments are given in Table 3. The failure rate calculations can be determined by the hardware components are as follows; IXTK 62N 25 for two MOSFET's, RF1001 for diodes D1, D2, D3 and D4, MUR1560 for D5, D6 and D0, electrolytic type for C1, C2, C3 and C0 and aluminium type for C4 and C5. The values of supporting parameters like  $R_{DS(ON)}$ ,  $T_C$ ,  $\theta_{JC}$ ,  $T_J$  and  $\theta_{JC}$  are taken from the data sheets of hardware components.

Table 2. Failure rates and stress factors [26]

Components	Equations of failure rate	Equations of stress factor
MOSFET	$\lambda = \lambda_b \pi_\tau \pi_A \pi_Q \pi_E \text{ Failures}/10^6$	$\pi_\tau = \exp \left[ -1925 \left( \frac{1}{T_j + 273} - \frac{1}{298} \right) \right]$ $T_j = T_c + \theta_{jc} \cdot P_d$
Diode	$\lambda = \lambda_b \pi_\tau \pi_s \pi_c \pi_E \text{ Failures}/10^6$	$\pi_\tau = \exp \left[ 3091 \left( \frac{1}{T_j + 273} - \frac{1}{298} \right) \right]$ $T_j = T_c + \theta_{jc} \cdot P_d$
Capacitor	$\lambda = \lambda_b \pi_{cv} \pi_Q \pi_E \text{ Failures}/10^6$ $\pi_{cv} = 0.34 C^{0.18}$	$\lambda_b = \left[ \left( \frac{s}{0.5} \right)^2 \right] \cdot \exp \left[ 5.09 \left( \frac{T_A + 273}{378} \right)^5 \right]$
Inductor	$\lambda = \lambda_b \pi_Q \pi_E \pi_C$	$\lambda_b = 0.00035 \exp \left( \frac{T_{HS} + 273}{409} \right)$ $T_{HS} = T_A + 1.1 \Delta T, \Delta T = \frac{125 W_L}{A}$

The junction temperature of switches S1, S2 and all diodes from D0 to D6 of proposed converter can determined by using:

$$T_j = T_c + \theta_{jc} \cdot P_d \quad (3)$$

where  $T_j$  is worst case junction temperature ( $^{\circ}\text{C}$ ),  $T_c$  is case temperature ( $^{\circ}\text{C}$ ),  $\theta_{jc}$  is junction to case thermal resistance ( $^{\circ}\text{C/W}$ ) and  $P_d$  is power dissipation (W). The stress factors for all the components of proposed converter is determined by referring MIL-HDBK-217 military handbook [26] and specifications of hardware components in Table 3. By substituting the failure rate of hardware components in (2). The failure rate of converter can be determined by,  $\lambda_{\text{converter}} = 40.78 \times 10^6$  hours.

$$MTBF = 24520 \text{ hours}$$

The stress factors and predicted failure rate of hardware components are tabulated in Table 4. The predicted failure rate of switches S1, S2 are  $0.768 \times 10^{-6} h^{-1}$ , the diodes D1, D2, D3, D4 are  $6.72 \times 10^{-6} h^{-1}$ , diodes D5, D6, D0 are  $1.232 \times 10^{-6} h^{-1}$ , the capacitors C1, C2 are  $1.33 \times 10^{-3} \times 10^{-6} h^{-1}$ , the capacitor C3 are  $1.209 \times 10^{-3} \times 10^{-6} h^{-1}$  capacitors C0 are  $31.89 \times 10^{-3} \times 10^{-6} h^{-1}$  and inductors are  $2.52 \times 10^{-3} \times 10^{-6} h^{-1}$ . The mean time between failures of proposed high gain converters are found to be 24520 hours. The results show that the proposed high-gain converter is moderately reliable. A novel and high-gain converter has been developed and tested for renewable energy applications, and perhaps it is generally reliable.

Table 3. Essential parameters and selected values for failure rate assessments

Components	Parameters and values
MOSFET's S1, S2	IXTK 62N 25 ( $R_{DS(on)} = 35 \text{ m}\Omega$ , $T_c = 25^{\circ}\text{C}$ , $\theta_{jc} = 0.3^{\circ}\text{C/W}$ )
The diodes D1, D2, D3, D4	RF1001 ( $T_c = 25^{\circ}\text{C}$ , $T_j = 150^{\circ}\text{C}$ , $\theta_{jc} = 3.5^{\circ}\text{C/W}$ , $P_d = 8.98 \text{ W}$ )
The diodes D5, D6, D0	MUR1560 ( $T_c = 25^{\circ}\text{C}$ , $T_j = 175^{\circ}\text{C}$ , $\theta_{jc} = 1.5^{\circ}\text{C/W}$ )
The capacitors C1, C2, C3	Electrolytic (200 V, 5 A) (1–10 $\mu\text{F}$ )
The capacitors C4, C5	Aluminum type (300 V, 10 A), 650 nF
The capacitors C0	Electrolytic type (250 V, 5 A) 470 $\mu\text{F}$

Table 4. Stress factors and predicted failure rate for each component

Stress factors	Switches S1 and S2	Diodes D1, D2, D3, D4	Diodes D5, D6, D0	Capacitors C1, C2	Capacitors C3	Capacitors C4, C5	Capacitors C0	Inductors
$\lambda_b$	0.012	0.069	0.069	0.031	0.031	0.031	0.031	$5.38 \times 10^{-4}$
$\pi_A$	8	—	—	—	—	—	—	—
$\pi_s$	—	0.58	0.77	—	—	—	—	—
$\pi_c$	—	1	1	—	—	—	—	1
$\pi_Q$	8	8	1	0.1	0.1	1.0	1.0	4
$\pi_E$	1	1	1	1.0	1.0	1.0	1.0	1
$\pi_T$	1.08	21	23.2	—	—	—	—	—
$\pi_{cv}$	—	—	—	0.43	0.39	0.314	1.029	—
Predicted failure rate $10^{-6} h^{-1}$	0.768	6.72	1.232	$1.333 \times 10^{-3}$	$1.209 \times 10^{-3}$	$9.734 \times 10^{-3}$	$31.89 \times 10^{-3}$	$2.52 \times 10^{-3}$

### 3.1. Effect of failure rates of components

Figure 3 shows the contributions of each component to the converter failure rate of proposed high gain converter. The contribution of failure rate of switches S1, S2 are 8.8%, diodes D1, D2, D3 and D4 are found to be 77.06%, D5, D6, D0 are 14.12%, C1 and C2 is 0.15%, C3 is 0.01%, C4, C5 is 0.36% and inductors 0.29%. In the presented reliability assessments, the failure rates corresponding to the diodes have higher chances of failure. Therefore, diodes with different characteristics are to be selected for better reliability.




Figure 3. Contributions of each component to the converter failure rate

## 4. CONCLUSION

In this paper, the reliability of a novel high-gain converter is investigated. The reliability of DC converters is influenced by a variety of elements, including component quality, design considerations, operating circumstances, and maintenance procedures. The reliability evaluation of the proposed converter is done and it is found that the diodes have the highest failure rate. The failure rate of the proposed topology is calculated using the military handbook and it is observed that the failure rate is 24520 hours. The results show that the proposed high-gain converter is moderately reliable and reliability can be improved by replacing the diodes with different characteristics. However, reliability is a dynamic, ever-evolving characteristic rather than a static one. To guarantee that these systems operate reliably in their intended applications, regular evaluations and enhancements are required.





## REFERENCES

- [1] M. Forouzesh, Y. P. Siwakoti, S. A. Gorji, F. Blaabjerg, and B. Lehman, "Step-Up DC-DC converters: A comprehensive review of voltage-boosting techniques, topologies, and applications," *IEEE Transactions on Power Electronics*, vol. 32, no. 12, pp. 9143–9178, Dec. 2017, doi: 10.1109/TPEL.2017.2652318.
- [2] M. S. Bhaskar *et al.*, "Survey of DC-DC non-isolated topologies for unidirectional power flow in fuel cell vehicles," *IEEE Access*, vol. 8, pp. 178130–178166, 2020, doi: 10.1109/ACCESS.2020.3027041.
- [3] F. L. Tofoli, D. de C. Pereira, W. J. de Paula, and D. de S. Oliveira Júnior, "Survey on non-isolated high-voltage step-up dc-dc topologies based on the boost converter," *IET Power Electronics*, vol. 8, no. 10, pp. 2044–2057, Oct. 2015, doi: 10.1049/iet-pel.2014.0605.
- [4] W. Li and X. He, "Review of nonisolated high-step-up DC/DC converters in photovoltaic grid-connected applications," *IEEE Transactions on Industrial Electronics*, vol. 58, no. 4, pp. 1239–1250, Apr. 2011, doi: 10.1109/TIE.2010.2049715.
- [5] P. R. Bana, K. P. Panda, R. T. Naayagi, P. Siano, and G. Panda, "Recently Developed Reduced Switch Multilevel Inverter for Renewable Energy Integration and Drives Application: Topologies, Comprehensive Analysis and Comparative Evaluation," *IEEE Access*, vol. 7, pp. 54888–54909, 2019, doi: 10.1109/ACCESS.2019.2913447.
- [6] X. Hu and C. Gong, "A high gain input-parallel output-series DC/DC converter with dual coupled inductors," *IEEE Transactions on Power Electronics*, vol. 30, no. 3, pp. 1306–1317, Mar. 2015, doi: 10.1109/TPEL.2014.2315613.
- [7] A. Ghosh and S. S. Saran, "High gain DC-DC step-up converter with multilevel output voltage," in *2018 International Symposium on Devices, Circuits and Systems, ISDCS 2018*, IEEE, Mar. 2018, pp. 1–6, doi: 10.1109/ISDCS.2018.8379657.
- [8] F. M. Shahir, E. Babaei, and M. Farsadi, "Analysis and design of voltage-lift techniquebased non-isolated boost dc-dc converter," *IET Power Electronics*, vol. 11, no. 6, pp. 1083–1091, May 2018, doi: 10.1049/iet-pel.2017.0259.
- [9] B. P. Baddipadiga and M. Ferdowsi, "A High-Voltage-Gain DC-DC Converter Based on Modified Dickson Charge Pump Voltage Multiplier," *IEEE Transactions on Power Electronics*, vol. 32, no. 10, pp. 7707–7715, Oct. 2017, doi: 10.1109/TPEL.2016.2594016.
- [10] H. S. H. Chung, A. Ioinovici, and W. L. Cheung, "Generalized structure of bi-directional switched-capacitor DC/DC converters," *IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications*, vol. 50, no. 6, pp. 743–754, Jun. 2003, doi: 10.1109/TCSI.2003.812615.





- [11] B. Yang, W. Li, Y. Zhao, and X. He, "Design and analysis of a grid-connected photovoltaic power system," *IEEE Transactions on Power Electronics*, vol. 25, no. 4, pp. 992–1000, Apr. 2010, doi: 10.1109/TPEL.2009.2036432.
- [12] Y. P. Hsieh, J. F. Chen, T. J. Liang, and L. S. Yang, "A novel high step-up DC-DC converter for a microgrid system," *IEEE Transactions on Power Electronics*, vol. 26, no. 4, pp. 1127–1136, Apr. 2011, doi: 10.1109/TPEL.2010.2096826.
- [13] A. M. S. S. Andrade, R. C. Beltrame, L. Schuch, and M. L. D. S. Martins, "PV module-integrated single-switch DC/DC converter for PV energy harvest with battery charge capability," in *2014 11th IEEE/IAS International Conference on Industry Applications, IEEE INDUSCON 2014 - Electronic Proceedings*, IEEE, Dec. 2014, pp. 1–8, doi: 10.1109/INDUSCON.2014.7059459.
- [14] F. Sebaaly, H. Vahedi, H. Y. Kanaan, N. Moubayed, and K. Al-Haddad, "Design and Implementation of Space Vector Modulation-Based Sliding Mode Control for Grid-Connected 3L-NPC Inverter," *IEEE Transactions on Industrial Electronics*, vol. 63, no. 12, pp. 7854–7863, Dec. 2016, doi: 10.1109/TIE.2016.2563381.
- [15] R. Palanisamy and K. Vijayakumar, "Paper SVPWM for 3-phase 3-level neutral point clamped inverter fed induction motor control," *Indonesian Journal of Electrical Engineering and Computer Science*, vol. 9, no. 3, pp. 703–710, Mar. 2018, doi: 10.11591/ijeecs.v9.i3.pp703-710.
- [16] S. A. Zaid *et al.*, "From MPC-Based to End-to-End (E2E) Learning-Based Control Policy for Grid-Tied 3L-NPC Transformerless Inverter," *IEEE Access*, vol. 10, pp. 57309–57326, 2022, doi: 10.1109/ACCESS.2022.3173752.
- [17] J. Lyu, J. Wang, W. Hu, and Y. Yan, "A Neutral-point voltage controller with hybrid parameters for npc three-level grid-connected inverters under unbalanced grid conditions," *IEEE Journal of Emerging and Selected Topics in Power Electronics*, vol. 8, no. 4, pp. 4367–4381, Dec. 2020, doi: 10.1109/JESTPE.2019.2930570.
- [18] R. Palanisamy, K. Vijayakumar, A. Bagchi, V. Gupta, and S. Sinha, "Implementation of Coupled Inductor Based 7-level Inverter with Reduced Switches," *International Journal of Power Electronics and Drive Systems (IJPEDS)*, vol. 8, no. 3, p. 1294, Sep. 2017, doi: 10.11591/ijpeds.v8.i3.pp1294-1302.
- [19] A. Khosroshahi, M. Abapour, and M. Sabahi, "Reliability evaluation of conventional and interleaved DC-DC boost converters," *IEEE Transactions on Power Electronics*, vol. 30, no. 10, pp. 5821–5828, Oct. 2015, doi: 10.1109/TPEL.2014.2380829.
- [20] L. Palma and P. N. Enjeti, "A modular fuel cell, modular DC-DC converter concept for high performance and enhanced reliability," *IEEE Transactions on Power Electronics*, vol. 24, no. 6, pp. 1437–1443, Jun. 2009, doi: 10.1109/TPEL.2009.2012498.
- [21] J. Sakly, A. Bennani-Ben Abdelghani, I. Slama-Belkhdja, and H. Sammoud, "Reconfigurable DC/DC Converter for Efficiency and Reliability Optimization," *IEEE Journal of Emerging and Selected Topics in Power Electronics*, vol. 5, no. 3, pp. 1216–1224, Sep. 2017, doi: 10.1109/JESTPE.2017.2676027.
- [22] M. J. Sathik, J. D. Navamani, A. Lavanya, Y. Yang, D. Almakhlles, and F. Blaabjerg, "Reliability Analysis of Power Components in Restructured DC/DC Converters," *IEEE Transactions on Device and Materials Reliability*, vol. 21, no. 4, pp. 544–555, Dec. 2021, doi: 10.1109/TDMR.2021.3116941.
- [23] A. V. Katore and A. P. Munshi, "Reliability Evaluation of Multi-level Boost Converter," in *Proceedings - 2018 International Conference on Smart Electric Drives and Power System, ICSEDPS 2018*, IEEE, Jun. 2018, pp. 317–322, doi: 10.1109/ICSEDPS.2018.8536010.
- [24] V. Mulpuri, M. Haque, M. N. Shaheed, and S. Choi, "Multistate Markov Analysis in Reliability Evaluation and Life Time Extension of DC-DC Power Converter for Electric Vehicle Applications," in *2018 IEEE Transportation and Electrification Conference and Expo, ITEC 2018*, IEEE, Jun. 2018, pp. 737–743, doi: 10.1109/ITEC.2018.8450102.
- [25] R. Subbulakshmy and R. Palanisamy, "SVPWM control strategy for Novel Interleaved High Gain DC converter fed 3-level NPC Inverter for Renewable Energy Applications," *ISA Transactions*, vol. 140, pp. 426–437, Sep. 2023, doi: 10.1016/j.isatra.2023.05.019.
- [26] "Reliability prediction of electronic equipments," in *Military Handbook*, Greensburg, PA, USA, Tech.: Relux Software Corp, 1991.

## BIOGRAPHIES OF AUTHORS



**Subbulakshmy Ramamurthi**     received her B.E. (EEE) and M.E (PED) from Mailam Engineering College (affiliated with Anna University, Chennai, India) in 2007 and 2009. Now she is doing her Ph.D. in SRMIST (formerly SRM University) Kattankulathur, India. Her current research interests includes DC converters and multilevel inverters. She can be contacted at email: sr2381@srmist.edu.in.



**Palanisamy Ramasamy**     received the B.E. degree in Electrical and Electronics Engineering from Anna University, India, in 2011, and the M.Tech. degree in Power Electronics and Drives and the Ph.D. degree in Power Electronics from the SRM Institute of Science and Technology, Chennai, India, in 2013 and 2019, respectively. He is currently working as an assistant professor with the Department of Electrical Engineering, SRM Institute of Science and Technology. He has published more than 95 international and national journals. His research interests include power electronics multilevel inverters, various PWM techniques for power converters, FACTS controllers, and grid connected photovoltaic systems. He can be contacted at email: palanis@srmist.edu.in.